

# ICIP-3000CCD-W

3 Megapixel Indoor, Box Network Camera

---



High resolution, feature rich, and a powerful imager – the ICIP-3000CCD-W is a unique box style IP camera. The camera itself captures a stunning 3MP resolution, thanks to its powerful 1/3" CCD imager. By utilizing a CCD sensor, this camera has excellent lowlight capabilities, and is rather IR sensitive. Further, this camera standardly includes a Wi-Fi module for pairing to wireless networks.

## Features

- 1/3" CCD 3.0 Megapixels
- Supports DC12V/AC24V dual power supply, PoE
- Supports max 32GB SD card for local storage
- Supports Alarm I/O, RS485 interface

# ICIP-3000CCD-W

## Specifications

<b>Model</b>	ICIP-3000CCD-W
<b>General</b>	
Processor	TI DaVinci Series DSP
Operating System	Embedded LINUX
Resource	Simultaneous remote monitoring, local recording and remote control
User Interface	Web, Smart ICRSS, ICRSS Pro/ICVIEW, NVR
<b>Camera</b>	
Image Sensor	1/3" CCD 3.0 Megapixels
Effective Pixels	2096(H)x1561(V)
Electronic Shutter	Auto/Manual, 1/60~1/10000s
Signal Noise Ratio	>50dB
Gain Control	Auto/Manual
White Balance	Auto/Manual
Day/Night	ICR
Lens	CS mount
<b>Video</b>	
Video Compression	H.264E / MJPEG
Image Resolution	3.0MP (2048x1536) / 1080P (1920x1080) / 720P (1280x720) / D1 (704x480) / CIF (352x240) / VGA (640x480)
Encoding Speed	Main Stream: 3.0MP (1 ~ 20fps), 1080P/720P/ D1/CIF/VGA (1 ~ 30fps) Extra Stream: D1/CIF (1 ~ 30fps)
Bit Rate	160K ~ 8Mbps
Snapshot	Fastest 1fps JPEG capture
Video Format	NTSC
Analog Video Output	1 channel BNC (1.0Vp-p, 75Ω)
<b>Audio</b>	
Audio Compression	G.711a / G.711u / PCM
Bit Rate	64kbps/128kbps
Input	1 channel RCA
Output	1 channel RCA
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Network Functions	HTTP, TCP/IP, ARP, IGMP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPOE, UPnP, NTP, Bonjour, SNMP
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade
<b>Auxiliary Interface</b>	
SD Card	Max 32GB, local storage
Alarm	2 Input / 1 Output
<b>Environmental</b>	
Power Supply	DC12V/AC24V, PoE
Power Consumption	<10W
IR LEDs	60~100 ft
Ingress Protection	IP66
Operating Environment	-14°F ~ 140°F / -25°C ~ 60°C, 10%~90%



Dimensions (WxDxH)	11.35"x4.66"x3.98"/288.3mmx118.3mmx101mm
Weight	6lb/2.5kg

# ICIP-3000CCD-W

---

## Accessories



[OUTDOOR HOUSING](#)



[M4](#)