

IHX-C1202B

Apartment Outdoor Station (Black)



Features

- A 3" STN screen
- Black-crystal glass panel with touch buttons
- Adoptive TCP/IP network host, supports SNMP network protocol
- Network security technology, provides stable and safe operating environment
- Supports night vision & voice indication
- Embedded installation
- Supports card and password to open the door
- IP65

IHX-C1202B

Specifications

Model	IHX-C1202B
System	
Main Processor	Embedded micro processor
Operating System	Embedded LINUX OS
Video	
Video Compression Standard	H.264
Input/Approaching Induction	1.3 megapixel CMOS camera
Black Light	Support
Auto Light Compensation	Support
Audio	
Input	Microphone
Output	Built-in speaker
Bi-directional Talk	Supported
Display	
LCD Dimensions	3" STN screen
Resolution	128×64
Operating Modes	
Input	Touch keyboard
Card	Built-in IC card induction reader
Approaching Induction	
Body Approaching	3'
Alarm	
Vandal Proof	Support
Access Control	
NO Output	Support
NC Output	Support
Door On/Off Button	Support
Door Status Detect	Support
Network	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
Storage	
Memory	128MB
General	
Power	DC 10 ~ 15V
Power Consumption	Standby ≤1W, work ≤10W
Working Environment	-40°F ~ 140°F/-40°C ~ 60°C; 10% ~ 95%RH
Weather Rated	IP65
Dimensions	16.06"×5.91"×2.33"/408mm×150mm×59.1
Weight	3.53lbs/1.6kg

IC Realtime LLC
 3050 N Andrews Avenue Extension
 Pompano Beach, FL 33064
 (866) 997-9009

www.icrealtime.com

Designs and specifications subject to change without notice. Copyright © 2015 IC Realtime, LLC. All rights reserved