

IPND-B80V-IRW1

8MP 2x Zoom IR Bullet Network Camera



Camera Specifications

Image Sensor	1/1.8" Progressive CMOS
Maximum Resolution	3840x2160 (8MP)
Lens Type	Vari-focal Auto Focus
Focal Length	f = 4.3 ~ 9.8mm
Aperture	F1.6 ~ F2.6
Iris Type	P-iris
Field of View	110.4° ~ 45.1° (Horizontal) 57.9° ~ 25.4° (Vertical) 133.9° ~ 51.8° (Diagonal)
Shutter Speed	1/5 sec. to 1/32,000 sec.
WDR	WDR Pro
Day / Night	Yes
Removable IR-Cut Filter	Yes

Camera Specifications (cont'd)

Illuminators	4x LEDs - Up to 40 meters with Smart IR
Minimum Illumination	0.02 lux @ F1.6 (Color) <0.005 lux @ F1.6 (B/W) 0 lux with IR illumination on
Tilt Range	80°
Rotation Range	350°
Storage	MicroSD up to 1TB capacity NAS (network attached storage)
Remote Control	Remote focus, remote zoom, pixel calculator

Video Specifications

Compression	H265, H264, MJPEG
Maximum Frame Rate	30 fps @ 3840x2160 (8MP)
Number of Streams	3 video streams (Up to 8 configurable profiles)
Signal to Noise Ratio	54 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and constrained bit rate control, Smart Stream III
Image Settings	General settings video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings Illuminators illuminators, anti-overexposure

Video Specifications (cont'd)

Image Settings	Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR, EIS (built-in gyro sensor), scene mode (auto, deblur)
	Exposure BLC, HLC, exposure control (exposure level, iris adjustment, exposure time, gain control, iris mode), AE speed adjustment, WDR
	Focus zoom, focus
	Privacy mask Pixel calculator Scheduled profile settings

Audio Specifications

Audio Capability	Two-Way Audio (full duplex)
Audio Compression	G.711, G.726, MPEG-2 AAC-LC
Audio Interface	Built-in microphone (effective range 5 meters) External microphone Input External line output

Network Specifications

Users	Live streaming for up to 10 users / devices
Security	Access list, CSRF protection, digest authentication, HTTPS , IEEE 802.1x, Password protection, secure boot, signed firmware, user access log, user account management, Trusted Platform Module (TPM)
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP/SFTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, , NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2/1.3, UDP, UPnP

Network Specifications (cont'd)

Interface	10Base-T/100Base-TX Ethernet (RJ-45)
-----------	--------------------------------------

Onvif	Profile G, S, T, M supported
-------	------------------------------

AI Analytic Specifications

Processing Capability	Custom SoC with built-in hardware learning accelerator
-----------------------	--

Object Detection

People, Vehicle (4-wheeled, 2-wheeled), Human / Vehicle
Best shot, Path Extraction

Vision Object Analytics	Attribute Extraction People (gender, clothing color, bag, hat), Vehicle (bike, bus, car, motorcycle, truck, color) Human face Best shot, Re-Search Extraction
-------------------------	--

Attribute Extraction

IC Secure Analytics	Deep Learning VCA (Advanced Smart Tracking) Smart VCA - Package 1 Smart VCA (Intrusion detection, Loitering detection, Line crossing detection, face detection) Smart VCA - Package 2 Unattended object detection, Missing object detection
---------------------	--

Smart VCA - Package 1**Smart VCA - Package 2**

RealSight Engine	Smart IR III, Deblur, WDR, White Balance, Exposure Control
------------------	--

Alarm and Events

Event Triggers	Audio detection, camera tampering detection, digital input, manual trigger, motion detection, periodical trigger, recording notification, SD card life expectancy, shock detection, system boot
----------------	---

Event Actions	Event notification via audio clip, camera link, digital output, email, HTTP, FTP/SFTP, NAS server, SD card File upload via email, HTTP, FTP/SFTP, NAS server, SD card
---------------	---

General Information	
Connectors	RJ-45 cable connector for 10/100 Mbps Network/PoE connection Audio line input Audio line output Digital input: 1 Digital output *1 (DO+: 12V, 50mA; DO-: 30V, Open Drain, 1A)*
Indicators	System power and status indicator
Power Interface	IEEE 802.3af PoE Class 3
Power Consumption	Max. 12.4W (IR on) / 9.6W (off)
Dimensions	92 x 258.5 mm
Weight	1.04 kg
Certifications	EMC CE (EN55032, EN55035 Class A), UKCA (BS EN 55032/BS EN 55035 Class A), FCC (FCC Part 15 Subpart B Class A) Safety UL (UL62368-1), CB (IEC/EN 62368-1, IEC/EN 62368-1, IEC/EN 62471) Environment IK10, IP67
Operating Temperatures	Starting Temperature: -20°C ~ 50°C (-4°F ~ 122°F) Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) (IR off) -35°C ~ 50°C (-31°F ~ 122°F) (IR on)
Humidity	98% RH (non-condensing)

System Compatibility	
Operating Systems	Microsoft Windows 11 / 10 / 8 / 7 MacOS 10.12 - 26 (Chrome only)
Web Browsers	Chromium 58.0 or above (Chrome, Edge, Brave) Internet Explorer 10 / 11
3rd Party Video Players	VLC: 1.1.11 or higher
Accessories	
In the box	Quick installation guide, alignment sticker, screw pack, cable gland
DORI (EN 62676-4 Standard)	
Detection (25PPM / 8PPF)	Wide: 88.1 m (289.2 ft) Tele: 197.6 m (648.2 ft)
Observation (63PPM / 19PPF)	Wide: 35.0 m (114.9 ft) Tele: 77.9 m (255.7 ft)
Recognition (125PPM/ 38PPF)	Wide: 17.5 m (57.4 ft) Tele: 39.0 m (127.8 ft)
Identification (250PPM / 76PPF)	Wide: 8.7 m (28.6 ft) Tele: 19.5 m (63.9 ft)